

R C





The CI H20 EM INOX is a **professional hot pressure washer** featuring a compact structure and a robust stainless steel body. It is also very easy to handle, thanks to the four large wheels that facilitate the transport of this **high-pressure washer**.

CI H20 EM INOX is equipped with a powerful single-phase electric motor with magnetothermic protection that makes this hot water pressure washer performing, powerful and reliable in any condition of use.

Equipped with a high efficiency stainless steel hot box powered by fuel oil, the CI H20 EM INOX can supply hot water with a temperature of up to 150°C, therefore making it perfect for removing even the most stubborn dirt.

The components and technologies installed on this **professional pressure washer** allow it to guarantee a high performance and great durability over time. Because of this, the CI H20 EM INOX is therefore the perfect for the food, handicraft, industrial, and transport sectors.

THE ADVANTAGES OF CI H20 EM INOX

Many are the benefits CI H20 EM INOX can offer:

- Hot pressure washer with four large wheels with rubber treads that facilitate manoeuvrability and transportability
- Robust structure with stainless steel cover (AISI 430)
- Powerful single-phase electric motor with thermal-magnetic protection that makes the pressure washer highly performing, efficient and reliable
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic safety valve
- 3 24V pressure switches
- High efficiency stainless steel (AISI 430) hot box powered by fuel oil
- Adjustable pressure
- 150°C thermostat
- Stop&Go: when the machine is temporarily idle, it stops so as to

optimize consumption and reduce waste

- Switch-off system for: micro leaks, no water or if the motor overheats
- Low-voltage instrument panel
- Error, fuel oil, voltage and stop warning lights
- 24-litre fuel oil tank
- Built-in adjustable detergent suction
- Inspectionable water feed filter
- Comes with professional accessories: gun with protection and Swivel coupling, wand with high/low pressure head
- 1/4" MEG type nozzle with flat jet
- 10-metre reinforced high pressure tube
- Accessory holder and tube storage on the side

	Stop
(Go &

TECHNICAL DESCRIPTION		CI H20 EM INOX	
Max pressure	bar/psi	150/2200	
Max flow rate	l/h	600	
Туре	-	hot water	
∆°t	°C	55	
Power consumption	KW	3,0	
Power supply	V/Hz	230/50	
Motor	type/hp	single-phase electric with thermal-magnetic protection	
Rotation speed	rpm	1450	
Pump	type	ceramic piston with crank-rod system	
Pump head	material	brass	
Net weight	Kg	80	
Machine dimensions (lxhxw)	mm	1100x700x650	



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY Tel. 045 8774222 - www.comac.it - com@comac.it

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

